

FEATURES & SPECIFICATIONS

PRODUCT OVERVIEW

White thermoplastic emergency exit/unit combo.

CONSTRUCTION

Injection-molded, flame-retardant, high-impact, thermoplastic housing with snap-fit design components for easy installation. Universal J-box pattern. Universal chevrons are easily removed for directional indication. Fully assembled single face with extra faceplate for easy field-conversion to double face. Track and swivel arrangement permits full range of lamp adjustment.

LAMP DATA

LED expected life is more than 10 years. Two 5.4W DC T5 wedge-base lamps for emergency light. High-output option yields 12W extra capacity.

ELECTRONICS

Dual-voltage input 120V or 277V AC. Emergency combo provided with test switch, status indicator and rechargeable battery. Maintenance-free battery provides 90 minutes of emergency power.

LISTINGS

UL Listed. Meets UL 924, NFPA 101, NFPA 70-NEC and OSHA illumination standards. Indoor damp location (10°C to 40° C) listed standard.

WARRANTY

One-year warranty.

Catalog Number	
Notes	Туре

Exit-Unit Combos





ORDERING INFORMATION

Catalog Number	UPC	Description	Voltage	Wattage*	Pallet Oty.	Standard Carton Oty.	
ECR M6	745973431832	Red	120/277	5.4	72	6	
ECG M6	745973431894	Green	120/277	5.4	72	6	
ECR HO M6	745974173663	Red, high output	120/277	5.4	72	6	

*per lamp head

Emergency Sheet #: Combos





Lithonia Lighting