



<b>Model No.</b>	<b>VEC32120MR-1</b>
Ballast Type	Electronic
Family	Stratus
Input Voltage	120V
Lamp Operation	Parallel
Starting Method	Program Start

## PRODUCT SPECIFICATIONS

## ELECTRONIC BALLAST

Lamp Type	No. of Lamps	Input Voltage (V)	Input Current (A)	Input Power (W)	Power Factor	MAX THD (%)	Ballast Factor	Min. Starting Temp. (F)	Lamp Current Crest Factor	B.E.F.
FC12T9	1	120	0.50	31	0.50	135	1.00	0	1.7	3.23

### Performance:

- Meets ANSI Standard C82. 11-2005
- Meets ANSI Standard C62. 41-2002
- Meets FCC Part 18

### Safety:


- No PCB's
- UL and CUL Listed (Class P, Type 1 Outdoor)

### Application:

- Remote Mounting: 18ft. max. Lead length, 18AWG
- Maximum Ambient Temperature: 105F
- Sound Rated: A

### Physical Parameters

### Wiring Diagram



#### Enclosure

	in.
Length	3.90In
Width	2.0In
Height	1.2In
Mounting	3.50In
Weight	

#### Lead Length

	in.(+/-1.0)
Black	
White	
Red	
Blue	
Yellow	

Specification data is based on tests performed in a controlled environment and represents relative performance. Actual performance can vary depending on operating conditions. Application and performance data subject to change without notice. All specifications are nominal unless noted otherwise.



### ESPEN Technology, Inc.

12257 Florence Ave. • Santa Fe Springs, CA 90670  
 Phone: (562)529-2938 • Fax: (562)529-2978 • Toll Free: (866)933-7736  
 Email: info@espentech.com • www.espentech.com